MIRACLE SEALANTS

TRAVERTINE FILLER KIT

DESCRIPTION AND USES

Miracle Travertine Fill Kit permanently repairs holes, cracks and missing travertine fill. This easy-to-use kit contains a putty knife, mixing stick, and light and dark powder which can be mixed to create the desired color shade.

IDEAL SUBSTRATES

- Travertine
- Limestone
- Natural Stone

RECOMMENDED USES

Repairing holes, cracks or replacing missing fill in travertine surfaces.

- Counters
- Vanities
- Floors
- Backsplashes
- Tables
- Walls

PRODUCT FEATURES

- Repairs cracks and holes up to ¼" (6mm) and 1".(25mm) wide
- Matches most colors of travertine.
- Dries to a matte finish.
- Long lasting, durable fill

PRODUCT

SKU	DESCRIPTION
TRAVFIL6	Kit

PRODUCT INFORMATION

Read entire label and SDS before using.

NOTE: Always protect neighboring surfaces, including wood, carpet, metal, landscaping and other incompatible surfaces.

PRODUCT APPLICATION

DIRECTIONS

Be sure surface is dry, clean, and free of any foreign surface, wax, or sealer.

1) Using a small container and the supplied mixing stick, mix the fill material together with water to create a thick paste. Mix the light and dark material as needed to achieve desired color (light or dark material can also be used on their own if desired). Only mix as much material as can be used in 10-15 minutes. After 10-15 minutes of air exposure, your mix will begin to thicken and become difficult to work with.

2) Apply an even skim coat over surface and into holes using the supplied putty knife. Larger holes can be overfilled slightly to minimize shrinkage.

3) Allow Travertine Fill to completely dry on surface. This may require 10-15 minutes (depending on the area temperature and moisture).

4) After the material is completely dry, clean the excess material using a moist sponge. Wipe thoroughly to remove any residue from the surrounding areas.

NOTES: If the material is not dry when cleaning (see step 4), the moist sponge may remove some material from the holes you just repaired.

Repairing larger holes or cracks may require a polyester or epoxy resin.

ALWAYS PROVIDE A SAMPLE FOR APPROVAL. BE CERTAIN THAT THE EXPECTATIONS AND OVERALL RESULTS OF THIS PRODUCT ARE APPROVED PRIOR TO PRODUCT APPLICATION

ADDITIONAL PRODUCT INFORMATION

COVERAGE: Coverage will vary depending on size and number of holes or repairs.

HANDLING & STORAGE: Stored at 77°F (25°C) Travertine Filler Kit will have a shelf life of 36 months. Keep Travertine Filler Kit in the original container, properly sealed to avoid contamination.

DISPOSAL: Dispose of unused or unwanted product in accordance with local laws.

MAINTENANCE: For ongoing maintenance instructions please refer to Miracle Sealants Care Guide. Refer to the Miracle Sealants Product Recommendation Chart for specific product recommendations at www.rustoleum.com/miraclesealants.

TECHNICAL SUPPORT: For additional technical support, contact Miracle Sealants at 1-800-350-1901.

	TECHNICAL DATA	MS-48

MIRACLE SEALANTS

TRAVERTINE FILLER KIT

PHYSICAL PROPERTIES

	TRAVETINE FILLER KIT
Composition	Portland Cement, Crystalline Silica / Quartz, Titanium Dioxide, Calcium Sulfate
Volatile Organic Compounds	0%
Coverage	50-200 sq ft per pint
Shelf Life	3 years
Safety Information	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.