

Technical Data Sheet

Page 1 of 2

Properties:	<p>AKEMI® Acryclean is a highly pure solvent for residue-free cleaning of various surfaces.</p> <p>The product features and benefits are as following:</p> <ul style="list-style-type: none">- removes even stubborn silicone deposits- designed to leave a perfectly clean and contamination-free surface- evaporates without residues- removes adhesive residues without leaving residues																
Application Area:	<ul style="list-style-type: none">- for cleaning and degreasing of surfaces before bonding, sealing or coating- for the removal of grease, oil and silicone contamination, waxes, tar deposits, tree resin, sealant and adhesive residues- for the removal of stickers, foils and tapes- for smoothing and removal of sealants- also suitable for natural stone and many artificial stones																
Instructions for use:	<p>Cleaning and degreasing before bonding or coating applications:</p> <ol style="list-style-type: none">1. Spray AKEMI® Acryclean on the surface or apply with a cloth.2. Thoroughly wipe dry with a clean cloth.3. Allow to flash off for 5 to 10 minutes before bonding or coating. <p>Removal of adhesives or sealants:</p> <ol style="list-style-type: none">1. Remove residues of adhesives or sealants mechanically as far as possible.2. Wet residues thoroughly with AKEMI® Acryclean.3. Allow to work for 5 to 10 minutes.4. Remove residues with a cloth or a brush. <p>Removal of adhesives:</p> <ol style="list-style-type: none">1. Wet the adhesive residues thoroughly with AKEMI® Acryclean.2. Allow to work for 2 to 10 minutes.3. Remove the loosened residues.																
Special Notes:	<ul style="list-style-type: none">- For professional use only.- Not suitable for all plastic or painted surfaces. Test compatibility on an inconspicuous area before use.- For proper waste disposal, the container must be completely emptied.- Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.																
Technical Data:	<table><tr><td>Base:</td><td>mixture of aliphatic and aromatic hydrocarbons</td></tr><tr><td>Colour:</td><td>colourless</td></tr><tr><td>Odour:</td><td>strong white spirit</td></tr><tr><td>Working temperature:</td><td>+10°C to +35°C</td></tr><tr><td>Density:</td><td>0.75 g/ml / 20°C (spray can) 0.80 g/ml / 20°C (can, canister, drum)</td></tr><tr><td>VOC</td><td></td></tr><tr><td>○ spray can:</td><td>746 g/l</td></tr><tr><td>○ can, canister, drum:</td><td>796 g/l</td></tr></table>	Base:	mixture of aliphatic and aromatic hydrocarbons	Colour:	colourless	Odour:	strong white spirit	Working temperature:	+10°C to +35°C	Density:	0.75 g/ml / 20°C (spray can) 0.80 g/ml / 20°C (can, canister, drum)	VOC		○ spray can:	746 g/l	○ can, canister, drum:	796 g/l
Base:	mixture of aliphatic and aromatic hydrocarbons																
Colour:	colourless																
Odour:	strong white spirit																
Working temperature:	+10°C to +35°C																
Density:	0.75 g/ml / 20°C (spray can) 0.80 g/ml / 20°C (can, canister, drum)																
VOC																	
○ spray can:	746 g/l																
○ can, canister, drum:	796 g/l																
Storage:	If stored in dry and cool condition (5 - 25°C/41 - 77°F) in its closed original container at least 24 months from production.																

TDS 04.24

Technical Data Sheet

Page 2 of 2

- Health & Safety:** Read Safety Data Sheet before handling or using this product.
- Important Notice:** The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information - as well as other oral or written technical advises - must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

TDS 04.24