

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2024

Version number 11 (replaces version 10)

Revision: 07.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name: **Acryclean**
- Article number: 87600, 87601, 87602
- UFI: EHM7-5FHC-A489-Q2R4

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Cleaner solvent

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg
- Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

- | | | |
|-------------------|-----------|--|
| Flam. Liq. 2 | H225 | Highly flammable liquid and vapour. |
| Acute Tox. 4 | H332 | Harmful if inhaled. |
| Skin Irrit. 2 | H315 | Causes skin irritation. |
| Eye Irrit. 2 | H319 | Causes serious eye irritation. |
| STOT SE 3 | H335-H336 | May cause respiratory irritation. May cause drowsiness or dizziness. |
| STOT RE 2 | H373 | May cause damage to organs through prolonged or repeated exposure. |
| Asp. Tox. 1 | H304 | May be fatal if swallowed and enters airways. |
| Aquatic Chronic 2 | H411 | Toxic to aquatic life with long lasting effects. |

- Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
- Storage: Store in a well-ventilated place. Keep cool.
Store in a well-ventilated place. Keep container tightly closed.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07 GHS08 GHS09

Signal word

Danger

(Contd. on page 2)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2024

Version number 11 (replaces version 10)

Revision: 07.05.2024

Trade name: Acryclean

(Contd. of page 1)

| | |
|---|---|
| · <u>Hazard-determining components of labelling:</u> | reaction mass of ethylbenzole and xylene Naphtha (petroleum), hydrotreated light |
| · <u>Hazard statements</u> | H225 Highly flammable liquid and vapour. H332 Harmful if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects. |
| · <u>Precautionary statements</u> | P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read carefully and follow all instructions. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist/vapours/spray. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves / eye protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. |
| · <u>2.3 Other hazards</u> | The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes. |
| · <u>Results of PBT and vPvB assessment</u> | |
| · <u>PBT:</u> | Not applicable. |
| · <u>vPvB:</u> | Not applicable. |
| · <u>Determination of endocrine-disrupting properties</u> | For information on endocrine disrupting properties see section 11. |

SECTION 3: Composition/information on ingredients· **3.2 Mixtures**· Description: Mixture: consisting of the following components.

(Contd. on page 3)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2024

Version number 11 (replaces version 10)

Revision: 07.05.2024

Trade name: Acryclean

(Contd. of page 2)

| | | |
|---|--|---------|
| · <u>Dangerous components:</u> | | |
| CAS: 64742-49-0 EC number: 920-750-0 Reg.nr.: 01-2119473851-33 | Naphtha (petroleum), hydrotreated light Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336 EUH066 | 50-100% |
| EC number: 905-588-0 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32 01-2119486136-34 | reaction mass of ethylbenzole and xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | 25-50% |
| · <u>Regulation (EC) No 648/2004 on detergents / Labelling for contents</u> | | |
| aromatic hydrocarbons, aliphatic hydrocarbons | | ≥30% |
| · <u>Additional information:</u> For the wording of the listed hazard phrases refer to section 16. | | |

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General information: Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness
Dizziness

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents:

Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:
Carbon monoxide (CO)
Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

- Protective equipment: Mount respiratory protective device.
- Additional information Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

(Contd. on page 4)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2024

Version number 11 (replaces version 10)

Revision: 07.05.2024

Trade name: Acryclean

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to penetrate the ground/soil.
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:** Fumes can combine with air to form an explosive mixture.
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Protect from frost.
Keep container tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2024

Version number 11 (replaces version 10)

Revision: 07.05.2024

Trade name: Acryclean

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**· Ingredients with limit values that require monitoring at the workplace:**reaction mass of ethylbenzole and xylene**

| | |
|-----|---|
| AGW | Short-term value: 442 mg/m ³ , 100 ppm |
| | Long-term value: 221 mg/m ³ , 50 ppm |
| H | |

· DNELs**64742-49-0 Naphtha (petroleum), hydrotreated light**

| | | |
|------------|-----------------------------|-----------------------------------|
| Oral | DNEL (Langzeit-wiederholt) | 699 mg/kg bw/day (BEV) |
| Dermal | DNEL (Langzeit-wiederholt) | 773 mg/kg bw/day (ARB) |
| | | 699 mg/kg bw/day (BEV) |
| Inhalative | DNEL (Langzeit-wiederholt) | 2,035 mg/m ³ Air (ARB) |
| | | 608 mg/m ³ Air (BEV) |

reaction mass of ethylbenzole and xylene

| | | |
|------------|-----------------------------|---------------------------------------|
| Oral | DNEL (Langzeit-wiederholt) | 1.6 mg/kg bw/day (BEV) |
| Dermal | DNEL (Langzeit-wiederholt) | 180-212 mg/kg bw/day (ARB) |
| | | 108 mg/kg bw/day (BEV) |
| Inhalative | DNEL (Kurzzeit-akut) | 289-442 mg/m ³ Air (ARB) |
| | | 260 mg/m ³ Air (BEV) |
| | DNEL (Langzeit-wiederholt) | 211-221 mg/m ³ Air (ARB) |
| | | 14.8-65.3 mg/m ³ Air (BEV) |

· PNECs**reaction mass of ethylbenzole and xylene**

| | |
|----------------|------------------------------|
| PNEC (wässrig) | 6.58 mg/l (KA) |
| | 0.327 mg/l (MW) |
| | 0.327 mg/l (SW) |
| | 0.327 mg/l (WAS) |
| PNEC (fest) | 2.31 mg/kg Trockengew (BO) |
| | 12.46 mg/kg Trockengew (MWS) |
| | 12.46 mg/kg Trockengew (SWS) |

· Additional information: The lists valid during the making were used as basis.**8.2 Exposure controls**· Appropriate engineering controls No further data; see section 7.· Individual protection measures, such as personal protective equipment· General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
 Use skin protection cream for skin protection.
 Clean skin thoroughly immediately after handling the product.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2024

Version number 11 (replaces version 10)

Revision: 07.05.2024

Trade name: Acryclean

(Contd. of page 5)

Hand protection

Short term filter device:

Filter AX

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

Material of gloves

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove materialValue for the permeation: Level \leq 6, 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

Vitoject (KCL, Art_No. 890)

Butyl rubber, BR

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Camatril (KCL, 730, 731, 732, 733)

Butoject (KCL, Art_No. 897, 898)

Butyl rubber, BR

Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

Eye/face protection

Tightly sealed goggles

(Contd. on page 7)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2024

Version number 11 (replaces version 10)

Revision: 07.05.2024

Trade name: Acryclean

(Contd. of page 6)

· **Body protection:** Use protective suit.**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**General Information

| | |
|---|------------------------------------|
| · <u>Colour:</u> | According to product specification |
| · <u>Odour:</u> | Specific type |
| · <u>Odour threshold:</u> | Not determined. |
| · <u>Melting point/freezing point:</u> | Undetermined. |
| · <u>Boiling point or initial boiling point and boiling range</u> | 98-140 °C |
| · <u>Flammability</u> | Not applicable. |
| · <u>Lower and upper explosion limit</u> | |
| · <u>Lower:</u> | 0.7 Vol % |
| · <u>Upper:</u> | 7 Vol % |
| · <u>Flash point:</u> | 2 °C |
| · <u>Auto-ignition temperature:</u> | 500 °C |
| · <u>Decomposition temperature:</u> | Not determined. |
| · <u>pH</u> | Not determined. |
| | Not applicable |
| · <u>Viscosity:</u> | |
| · <u>Kinematic viscosity</u> | Not determined. |
| · <u>Dynamic:</u> | Not determined. |
| · <u>Solubility</u> | |
| · <u>water:</u> | Not miscible or difficult to mix. |
| · <u>Partition coefficient n-octanol/water (log value)</u> | Not determined. |
| · <u>Vapour pressure at 20 °C:</u> | 30 hPa |
| · <u>Density and/or relative density</u> | |
| · <u>Density at 20 °C:</u> | 0.8 g/cm ³ |
| · <u>Relative density</u> | Not determined. |
| · <u>Vapour density</u> | Not determined. |

9.2 Other information

| | |
|--|---|
| · <u>Appearance:</u> | |
| · <u>Form:</u> | Fluid |
| · <u>Important information on protection of health and environment, and on safety.</u> | |
| · <u>Ignition temperature:</u> | Product is not selfigniting. |
| · <u>Explosive properties:</u> | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · <u>Solvent content:</u> | |
| · <u>Organic solvents:</u> | 100.0 % |
| · <u>Change in condition</u> | |
| · <u>Evaporation rate</u> | Not applicable. |

Information with regard to physical hazard classes

| | |
|--|-------------------------------------|
| · <u>Explosives</u> | Void |
| · <u>Flammable gases</u> | Void |
| · <u>Aerosols</u> | Void |
| · <u>Oxidising gases</u> | Void |
| · <u>Gases under pressure</u> | Void |
| · <u>Flammable liquids</u> | Highly flammable liquid and vapour. |
| · <u>Flammable solids</u> | Void |
| · <u>Self-reactive substances and mixtures</u> | Void |
| · <u>Pyrophoric liquids</u> | Void |
| · <u>Pyrophoric solids</u> | Void |

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2024

Version number 11 (replaces version 10)

Revision: 07.05.2024

Trade name: Acryclean

(Contd. of page 7)

| | |
|--|------|
| · <u>Self-heating substances and mixtures</u> | Void |
| · <u>Substances and mixtures, which emit flammable gases in contact with water</u> | Void |
| · <u>Oxidising liquids</u> | Void |
| · <u>Oxidising solids</u> | Void |
| · <u>Organic peroxides</u> | Void |
| · <u>Corrosive to metals</u> | Void |
| · <u>Desensitised explosives</u> | Void |

SECTION 10: Stability and reactivity

| | |
|--|---|
| · 10.1 Reactivity | No further relevant information available. |
| · 10.2 Chemical stability | |
| · <u>Thermal decomposition / conditions to be avoided:</u> | No decomposition if used according to specifications. |
| · 10.3 Possibility of hazardous reactions | No dangerous reactions known. |
| · 10.4 Conditions to avoid | No further relevant information available. |
| · 10.5 Incompatible materials: | No further relevant information available. |
| · 10.6 Hazardous decomposition products: | No dangerous decomposition products known. |

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

| | |
|-------------------------|---------------------|
| · <u>Acute toxicity</u> | Harmful if inhaled. |
|-------------------------|---------------------|

· LD/LC50 values relevant for classification:**ATE (Acute Toxicity Estimates)**

| | | |
|------------|----------|----------------------|
| Dermal | LD50 | 5,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 15.9-16.8 mg/l (rat) |

64742-49-0 Naphtha (petroleum), hydrotreated light

| | | |
|------------|----------|-----------------------|
| Oral | LD50 | >5,000 mg/kg (rat) |
| Dermal | LD50 | >2,800 mg/kg (rabbit) |
| | LD50 | >2,000 mg/kg (rat) |
| Inhalative | LC50/4 h | >23.3 mg/l (rat) |

reaction mass of ethylbenzole and xylene

| | | |
|------------|-------------|--------------------------------|
| Oral | LD50 | 3,523 mg/kg (rat) |
| | NOAEL-Werte | 250 mg/kg (rat) |
| Dermal | LD50 | 12,126 mg/kg (rabbit) |
| Inhalative | LC50/4h | 29,000 mg/m ³ (rat) |
| | LC50/4 h | 27.124 mg/l (rat) |

| | |
|--|--|
| · <u>Skin corrosion/irritation</u> | Causes skin irritation. |
| · <u>Serious eye damage/irritation</u> | Causes serious eye irritation. |
| · <u>Respiratory or skin sensitisation</u> | Based on available data, the classification criteria are not met. |
| · <u>Germ cell mutagenicity</u> | Based on available data, the classification criteria are not met. |
| · <u>Carcinogenicity</u> | Based on available data, the classification criteria are not met. |
| · <u>Reproductive toxicity</u> | Based on available data, the classification criteria are not met. |
| · <u>STOT-single exposure</u> | May cause respiratory irritation. May cause drowsiness or dizziness. |
| · <u>STOT-repeated exposure</u> | May cause damage to organs through prolonged or repeated exposure. |
| · <u>Aspiration hazard</u> | May be fatal if swallowed and enters airways. |

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2024

Version number 11 (replaces version 10)

Revision: 07.05.2024

Trade name: Acryclean

(Contd. of page 8)

· 11.2 Information on other hazards**· Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information**· 12.1 Toxicity****· Aquatic toxicity:****64742-49-0 Naphtha (petroleum), hydrotreated light**

| | |
|-----------|---|
| EC50/48h | 4.6-10 mg/l (daphnia magna) |
| EL50/72h | 10-30 mg/l (Pseudokirchneriella subcapitata) |
| LL50/96h | >13.4 mg/l (Oncorhynchus mykiss) |
| NOELR/72h | 10 mg/l (Pseudokirchneriella subcapitata) |
| NOEC/21d | 0.17 mg/l (daphnia magna) |
| LC50/96h | <10 mg/l (daphnia magna) 3-10 mg/l (Oncorhynchus mykiss) |

reaction mass of ethylbenzole and xylene

| | |
|-----------|--|
| LC50/24h | 1 mg/l (daphnia magna) (OECD 202) |
| EC50/48h | 3.2-9.5 mg/l (daphnia magna) (US EPA) |
| ErC50/72h | 4.9 mg/l (Pseudokirchneriella subcapitata) (OECD 201) |
| NOEC | 16 mg/l (BES) 1.3 mg/l (Oncorhynchus mykiss) |
| NOELR/72h | 0.44 mg/l (algae) |
| NOEC/21d | 1.57 mg/l (daphnia magna) (OECD 211) |
| NOELR/28d | 16 mg/l (bacteria) |
| EC50/72h | 1-10 mg/l (algae) 2.2 mg/l (selenastrum capricornutum) (OECD 201) |
| LC50/96h | 1-10 mg/l (fish) 86 mg/l (Leuciscus idus) 2.6 mg/l (Oncorhynchus mykiss) (OECD 203) 8.9-16.4 mg/l (pimephales promelas) |

· 12.2 Persistence and**degradability**

No further relevant information available.

· 12.3 Bioaccumulative potential

No further relevant information available.

· 12.4 Mobility in soil

No further relevant information available.

· 12.5 Results of PBT and vPvB assessment**· PBT:**

Not applicable.

· vPvB:

Not applicable.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects**· Remark:**

Toxic for fish

· Additional ecological information:**· General notes:**Do not allow product to reach ground water, water course or sewage system.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

(Contd. on page 10)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2024

Version number 11 (replaces version 10)

Revision: 07.05.2024

Trade name: Acryclean

(Contd. of page 9)

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

SECTION 13: Disposal considerations**· 13.1 Waste treatment methods****· Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:**· Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
Disposal must be made according to official regulations.

SECTION 14: Transport information**· 14.1 UN number or ID number****· ADR, IMDG, IATA**

UN3295

· 14.2 UN proper shipping name**· ADR**

3295 HYDROCARBONS, LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated light, XYLENES), ENVIRONMENTALLY HAZARDOUS, special provision 640D

· IMDG

HYDROCARBONS, LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated light, XYLENES), MARINE POLLUTANT

· IATA

HYDROCARBONS, LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated light, XYLENES)

· 14.3 Transport hazard class(es)**· ADR****· Class**

3 (F1) Flammable liquids.

· Label

3

· IMDG**· Class**

3 Flammable liquids.

· Label

3

· IATA**· Class**

3 Flammable liquids.

· Label

3

· 14.4 Packing group**· ADR, IMDG, IATA**

II

(Contd. on page 11)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2024

Version number 11 (replaces version 10)

Revision: 07.05.2024

Trade name: Acryclean

(Contd. of page 10)

| | |
|---|---|
| · 14.5 Environmental hazards: | Product contains environmentally hazardous substances: |
| · <u>Marine pollutant:</u> | Yes |
| · <u>Special marking (ADR):</u> | Symbol (fish and tree) Symbol (fish and tree) |
| · 14.6 Special precautions for user | Warning: Flammable liquids. |
| · <u>Hazard identification number (Kemler code):</u> | 33 |
| · <u>EMS Number:</u> | F-E,S-D |
| · <u>Stowage Category</u> | B |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · <u>Transport/Additional information:</u> | |
| · <u>ADR</u> | |
| · <u>Limited quantities (LQ)</u> | 1L |
| · <u>Excepted quantities (EQ)</u> | Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| · <u>Transport category</u> | 2 |
| · <u>Tunnel restriction code</u> | D/E |
| · <u>IMDG</u> | |
| · <u>Limited quantities (LQ)</u> | 1L |
| · <u>Excepted quantities (EQ)</u> | Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| · <u>UN "Model Regulation":</u> | UN 3295 HYDROCARBONS, LIQUID, N.O.S. (NAPHTHA (PETROLEUM), HYDROTREATED LIGHT, XYLENES), 3, II, ENVIRONMENTALLY HAZARDOUS |

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**· Directive 2012/18/EU· Named dangerous substances - ANNEX I

None of the ingredients is listed.

· Seveso categoryE2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS· Qualifying quantity (tonnes) for the application of lower-tier requirements

200 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements

500 t

· REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

(Contd. on page 12)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.05.2024

Version number 11 (replaces version 10)

Revision: 07.05.2024

Trade name: Acryclean

(Contd. of page 11)

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Information about limitation of use: Employment restrictions concerning pregnant and lactating women must be observed.
Employment restrictions concerning juveniles must be observed.

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 800.0 g/l

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Laboratory

· Date of previous version: 09.12.2022

· Version number of previous version: 10

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2