



Triton BK™ Backer Board Safety Data Sheet (SDS)

Section 1 – Product and Company Identification

Manufacturer: MiTek, Inc.

Products: Triton BK™, JetBacker™, JetBoard™

Address 770 Bradfield Rd. #575, Houston, TX 77044

Information Phone Number: 833-909-0839

Email: info@tritonwatertight.com

Website: tritonwatertight.com

Emergency Phone Number: 877-453-8868

Recommended use:

Triton BK™ boards are used for tile backer and flooring underlayment.

JetBoard™ is used for SIP's and structural construction applications

Product Type: Construction Sheathing

Chemical Family: Magnesium Cement

Synonyms: MOC cement, Magnesium Oxide cement, Magnesium Nanoceramic cement

TSCA Inventory Status: Not listed

Section 2 – Hazard Identification

Emergency Overview:

Hazard Symbol:



WARNING:

PROLONGED EXPOSURE TO DUST MAY CAUSE LONG TERM LUNG DAMAGE

This product contains very low levels of materials suspected to cause cancer. These materials are at such low levels in this product that there is no expected danger, however minimizing exposure to dust will eliminate any potential and is a good practice when cutting any construction material.

Route(s) of Entry: Skin (None), Eyes (Dust and Chip Form), Inhalation (Dust and Chip Form), Digestion (Dust and Chip Form)

Health Hazards (Acute and Chronic):

Eyes (Dust and Chip Form - Irritation Hazard)

Inhalation (Dust and Chip Form – Irritation Hazard)

Skin (Fiberglass may cause itching irritation)

Ingestion (No Known Hazard)

Carcinogenicity: No Known Toxicity Effects (Skin, Eyes, Inhalation, Ingestion)

Signs and Symptoms of Exposure: Skin (None), Eyes (Irritation), Inhalation (Coughing), Ingestion (None)

Medical Conditions Generally Aggravated by Exposure: Asthma (Inhalation Exposure of Dust Form and Combustion Products) (Avoid Inhalation)



Section 3 –Composition/ Information on Ingredients

Ingredient Name	CAS Number	Percent of Total Weight
Magnesium Oxide	1309-48-4	<50
Magnesium Chloride	7786-30-3	<20
Perlite	130885-09-5	<10
Expanded Polystyrene	9003-53-6	<2
Fiberglass Scrim	65997-17-3	<2
Quartz, crystalline silica	14808-60-7	<3

Section 4 – First-aid Measures

Emergency and First Aid Procedures: Skin (Wash with Soap and Water), Eyes (Immediately Flush with Water. Contact Physician if Irritation Persists), Inhalation (Remove to Fresh Air), Ingestion (Seek Professional Medical Advice. Do Not Induce Vomiting)

Section 5 – Fire-fighting Measures

Flash Point: Solid - Not Applicable
Flammable Limits: Solid - Not Applicable...keeps shape even after intense heat exposure
LEL: Solid - Not Applicable
UEL: Solid - Not Applicable
Extinguishing Media: None, E84 0/0 Rated; Does not burn.
Special Fire Fighting Procedures: none
Unusual Fire and Explosion Hazards: NONE

Section 6 – Accidental Release Measures

Steps to be taken in Case Material Is Released or Spilled: Beneficial to water and soil, no environmental concerns with release and disposal. Dust and Chips can be swept, scooped or vacuumed and removed. Sheets shall be collected and removed.
Waste Disposal Method: Follow Local, State and Federal Regulations for nonhazardous refuse waste.
Precautions to Be Taken in Handling and Storing: Protective Gloves to prevent skin irritations; careful not to touch eyes during handling of material.
Other Precautions: None

Section 7 – Handling and Storage

Restrictions on use: No known adverse chemical reactions.

Minimize dust exposure: If sawing and in a confined space a NIOSH dust mask is recommended

Respirator Recommendations

NIOSH

Up to 0.5 mg/m³

(APF=10) Any Particulate respirator equipped with an N95, or P95 filter (including N95, R95, and P95 filtered face pieces) except quarter-mask respirators. The following filters may also be used: N99, R99, P99, N100, R100, and P100.

Store products in manufacturer's unopened packaging bearing the brand name and manufacturer's identification until ready for installation. Materials should be stored on level supports off the ground to prevent sagging.



Cover loosely with Water proof material to prevent condensation from forming while protecting against weather, direct sunlight, surface contamination, and construction traffic. Never stack more than 4 pallets high for wooden pallets and 2 for steel pallets.

Section 8 – Exposure Controls/ Personal Protection

Skin Protection: Protective Gloves and Clothing

Eye Protection: Safety Glasses or Goggles

Respiratory Protection: NIOSH dust mask. See Section 7 for guidance

Ventilation: General under Standard Conditions. Local Exhaust is recommended in High Dust Formation Areas.

Other Protective Clothing or Equipment: None

Work/Hygienic Practices: General Clean-up After Exposure. Score and snap generates less dust than sawing, which minimizes nuisance dust.

Ingredients- Exposure Limits

Component	CAS Number	OSHA-PEL	ACGIH-TLV
Magnesium Oxide	1309-48-4	15 mg/m ³ (Nuisance Particulate)	10 mg/m ³ (Nuisance Particulate)
Perlite	130885-09-5	5mg/m ³ (Nuisance Dust)	10mg/m ³ (Total Nuisance Dust)
Fiberglass Scrim	65997-17-3	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)	5 mg/m ³ (inhalable) 1 f/cc (respirable fibers)
Expanded Polystyrene	9003-53-6	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)	5 mg/m ³ (inhalable) 3 mg/m ³ (respirable)
Quartz, crystalline silica	14808-60-7	50 mg/m ³ (total dust)	-

*The weight percent for Crystalline Silica represents total Crystalline Silica and not the respirable fraction.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Crystalline silica has a detection limit of 3% in solid products. At levels below this, it is not expected to have any adverse health effects or be detectable in the dust. EU has determined that levels of crystalline silica in products at levels about 10 wt.% are dangerous. The US has yet to set a product limit and only specifies dust exposure levels. These products contain less than 3% and it is reported only because it is detectable. It is contained as an impurity in the Magnesium Oxide and is not added. It has been considered previously under the Magnesium Oxide CAS number but has been added in the 2017 revisions for transparency to EU users.

Additional Information: Products listed in this SDS do not contain any form of Asbestos.

Section 9 – Physical and Chemical Properties

Boiling Point: Solid

Vapor Pressure (mm Hg): Solid

Vapor Density (AIR = 1): Solid

Solubility in Water: Solid

Specific Gravity (H₂O = 1): 0.85

Melting Point (°F): Blow torch applied for 30 minutes straight by local fire marshal with no significant side effects...also tested with flame temperatures of 1400 degrees Celsius

Heat Deflection Temperature: Not Available

Evaporation Rate (Butyl Acetate = 1): Solid

Appearance and Odor: Sheet



Section 10 – Stability and Reactivity

Stability: Stable (Non-reactive to known substances)
Conditions to Avoid: No Known Conditions
Incompatibility (Materials to Avoid): No Known Substances
Hazardous Decomposition or Byproducts: No Known Conditions
Hazardous Polymerization: No Known Conditions
Conditions to Avoid: No Known Conditions

Section 11 – Toxicological Information

All risk information above is basis the raw materials. This product has not toxic data.

Section 12 – Ecological Information

This product is safe for disposal and has no known adverse effects.

Section 13 – Disposal Considerations

Dispose of per federal, state and local government regulations. Recycle if possible.

Section 14 – Transport Information

Not regulated for transportation


Section 15 – Regulatory Information

US:

TSCA Inventory Status: Not listed
 EPCRA 311/312 (Hazard Categories): Acute

EU regulation declaration:

Hazard elements of the STOT RE 2 label for products containing quartz (fine fraction 1-10%) or cristobalite (fine fraction 1-10%)

<p>Warning</p>  <p>H 373: May cause damage to lungs through prolonged or repeated exposure via inhalation</p>
--

Section 16 – Other Information

This material is categorized as Non-Hazardous for transportation purposes. The information contained herein is accurate to the best of all available knowledge at the time of printing. Hazardous conditions due to alterations of the material have not been established.

The information contained in this data sheet is furnished in good faith and without warranty, representations, or inducement or license of any kind, except that it is accurate to the best of JetProducts' knowledge, or was obtained from sources believed by JetProducts to be reliable. The accuracy, adequacy or completeness of health and safety precautions set forth herein cannot be guaranteed, and



the buyer is solely responsible for ensuring that product is used, handled, stored and disposed of safely and in compliance with applicable federal, state or provincial and local laws. JetProducts disclaims liability for loss, damage or personal injury that arises from, or is in any way related to use of the information contained in this data sheet.